

# TPASS<sup>®</sup> HP II

## FEATURES



Accountability Key  
in Storage Position

Firefighter's  
ID Window

Eng. Co. 76  
DAVIS

Sound  
Resonating  
Ports, One on  
Each Side

Amber LEDs illuminate  
the Case when Unit  
is Active.

Alternating Amber and  
Red LEDs illuminate  
the Case in Pre-Alarm.

RED LEDs illuminate  
the Case when in  
Full Alarm.



Front View  
Shown Actual Size

Antenna

"D" Ring  
and Grip Clip

Back View

Tether

Alarm  
Button

**GRACE**  
INDUSTRIES, INC.  
*Solutions for Life Safety*

**MADE IN  
USA**

## ***TPASS*<sup>®</sup> *HP II* SIGNAL RECEIVER**

Features and Detailed Specifications	Description
NFPA Compliant and Intrinsically Safe	Third Party Tested to NFPA 1982 (PASS), 1998 edition. Certified UL913 for Class 1, Division 1, Group A, B, C and D Hazardous locations.
Auto-On Activation	Proprietary Tethered Accountability Key
Motion Sensing	Solid State Accelerometer
High Frequency 2 Way Radio	902-928 MHz No FCC License Required
Smart-Signal Technology - Proprietary	Each TPASS-3 EVACUATE is a Smart Repeater for critical signals providing superior in building performance
Complete Protection with or without SCBA	Stand alone system for all situations
Automatic Motion Sensing - Man Down Alarm Activation	30-35 seconds - Loud Audio Alarm and Alarm signal to Command Base and indicated on Command Screen
Manual Mode Alarm Activation (Panic Button)	Manual Push Button-Need Emergency Assistance
Confirmation of TPASS-3 Active	Visible Flashing LED lights
Check-in Status Signal	Periodic signal sent to Command Base
Temperature Sensing – Alarm	Optional
TPASS-HP II - Physical Attributes	
Dimensions (approximate)	Compact Size 2" W, 3-1/8" H, 1-1/2" deep
Weight (approximate)	8 oz. With Battery and W/O Accountability Key
Low Battery Alarm	Alarm @ 20% capacity (1 hr. minimum in alarm mode remaining)
Battery	9 volt Duracell MN 1604 recommended and included
Battery Life (approximate)	30 hours In Sensing Mode and 2-4 hours in Alarm Mode

**GRACE**  
INDUSTRIES, INC.  
*Solutions for Life Safety*

**1.800.204.7277**