

Features	SMS-H	RET-H	RET-H-HT
Transmits – EVAC ALL Comand to Grace Worn Devices and MS2000X	YES	YES*	YES*
Receives – MAYDAY PANIC Commands from Grace Worn Devices and MS2000X	YES	YES*	YES*
Recieves – and Displays Locator Beacon Information from Grace Worn Devices	YES	NO	NO
Displays up to 72 PASS with the ability to assign custom names	YES	NO	NO
16 open-collector configurable steering outputs	YES	NO	NO
Auxiliary Power Input – 12VDC/1A	YES	NO	NO
Powered Telephone Dialer Port – for use with ATD Automatic Telephone Dialer	YES**	NO	NO
FORM C Relay Outlet 12VDC/5A	YES	NO	NO
Switched Output on Alarm 12VDC/1A	YES	NO	NO
PASS Device Programmer	YES	NO	NO
Event Logger – ships with PC download Utility for extracting log files	YES	NO	NO
Wall Mount/Desktop Configuration	YES	NO	NO
Wall Mount Standard/Pole Mount Option		YES**	YES**
Battery Run Time – 24 Hours		NO	NO
Battery Run Time – 6 Hours in Alarm		NO	NO
AC Power Input 240VAC $\sqrt{**}$	120 VAC	NO	120 VAC
Automatic Telephone Dialer – Optional – Order Separately	YES	NO	NO
Heated Enclosure – for operation below 32°F – Optional	NO	NO	YES**