

	TPASS® 3		SuperCELL® SC500	
Features	TP3-H-R-AM	TP3-H-R	SC500-H-SM	SC500-H-LW
Receives EVAC Commands from Grace Monitoring Systems	YES	YES	YES	YES
Receives PAR Check Commands from Grace Monitoring Systems	YES	YES	YES	YES
Monitors Alarms from all other Grace devices	YES	NO	YES	YES
Transmits Motion Sensing Panic Alarm	YES	YES	YES*	YES
Transmits Manual Panic Alarm	YES	YES	YES*	YES
Receives/Transmits Canned Messages from Grace Devices	NO	NO	YES	YES
Capable of Disabling Motion Sensing	NO	NO	YES*	NO
Capable of Selecting Custom Motion Timing	NO	NO	YES*	NO
Manual Power On/Off	YES**	YES**	YES	NO
Auto Activation – Power On/Off Requires Accountability Key/Powered Cradle	YES**	YES**	NO	YES
Indoor Grace Locator Position Data *	YES	YES	YES	YES
Displays Indoor Grace Locator Position Data *	NO	NO	YES	YES
Interfaces with existing Mobile Lone Worker Telematics Systems	YES	YES	YES	YES
Select Motion Timing when ordering – 060, 090 or 120 second **	YES**	YES**	NO	YES**
Changes require return to the factory and service charge	YES**	YES**	NO	YES**
Rechargeable Operation	YES	YES	YES	YES
Recharge Time – 6-8 Hours	80 hr	80 hr	40 hr	40 hr
Charge Types – 12VDC, 120VAC or International – Select when ordering	YES**	YES**	YES**	YES**
Audio Sound Pressure (dBA) @ 10' when in PANIC/PAR/EVAC	92 dBA	92 dBA	75 dBA	75 dBA
Heavy Duty – IP67 Rated	YES	YES	YES	YES
Intrinsically Safe	YES	YES	YES	YES